

**W202P-2288INTEC**



**Product Data Sheet  
P/N W202P-2288INTEC**

**MADE IN USA**

**20AWG 2 PAIR STRANDED BC 1PAIR SHIELDED WITH 1PAIR 20AWG UNSHIELDED NATURAL JACKET  
UL TYPE CL3P/CMP**

**ELEMENT 1:**

<b>CONDUCTOR:</b>	<b>20 AWG 7 STRAND BARE COPPER</b>
<b>INSULATION:</b>	<b>PLENUM RATED PVC</b>
<b>CABLE:</b>	<b>2 CONDUCTORS TWISTED</b>
<b>COLOR CODE:</b>	<b>BLUE, GREEN</b>
<b>SHIELD:</b>	<b>ALUMINIUM/MYLAR TAPE – 100% COVERAGE WITH 24 AWG STRANDED TINNED COPPER DRAIN WIRE</b>
<b>ELECTRICALS:</b>	
<b>IMPEDANCE:</b>	<b>36 OHMS +/- 10%</b>
<b>CAPACITANCE:</b>	<b>52 Pf/FT +/- 10%</b>
<b>DC RESISTANCE:</b>	<b>10.4 OHMS/MFT @20C</b>

**ELEMENT 2:**

<b>CONDUCTOR:</b>	<b>20 AWG 7 STRAND BARE COPPER</b>
<b>INSULATION:</b>	<b>PLENUM RATED PVC</b>
<b>CABLE:</b>	<b>2 CONDUCTORS TWISTED</b>
<b>COLOR CODE:</b>	<b>BLACK, RED</b>
<b>ELECTRICALS:</b>	
<b>IMPEDANCE:</b>	<b>63 OHMS +/- 10%</b>
<b>CAPACITANCE:</b>	<b>30 Pf/FT +/- 10%</b>
<b>DC RESISTANCE:</b>	<b>10.4 OHMS/MFT @20C</b>

**OVERALL ASSEMBLY:**

<b>CABLE:</b>	<b>2 PAIRS TWISTED WITH 3.00" LHL (4.00 TW/FT)</b>	
<b>JACKET:</b>	<b>PLENUM RATED PVC NATURAL</b>	<b>OVERALL O.D.: .157" nom. WEIGHT: 23 LBS/M</b>
<b>JACKET PRINT:</b>	<b>INTEC CONTROLS (UL FILE#) 20 AWG 2 PR 75C (UL) CL3P OR FPLP OR C(UL)US CMP FT-6 "ROHS COMPLIANT" MADE IN USA (SEQUENTIAL FOOTAGE MARKERS)</b>	

**STANDARDS**

**CABLE SUITABLE FOR INSTALLATION UNDER NEC (NFPA 70) ARTICLES 800, 725 AN 760 GUIDELINES  
CABLE SUITABLE FOR INSTALLATION IN CANADA UNDER SECTIONS 60 OF CEC, PART 1  
C(UL)US LISTED AS CMP PER UL STANDARD 444 AND PER CSA C22.2 NO 214-17  
UL LISTED AS CL3P PER UL STANDARD 13 AND FPLP PER UL STANDARD 1424  
CABLE IS ROHS III COMPLIANT PER DIRECTIVE 2015/863/EU  
OPERATING VOLTAGE: 300V RMS**

**Created 4/18/18 kz  
Revised 8/30/2021 ju**