

## TOOL TYPES

PART NUMBER	DESCRIPTION
-------------	-------------

### PolyGard®2 Commissioning and Calibration Gas Kits

<b>CALKIT-PG2-CO</b>	Sensor calibration adapter w/ tube and cup, 500 mL/min. regulator, 17L 200 ppm carbon monoxide, 17L 99.99% nitrogen, carrying case
<b>CALKIT-PG2-COMB</b>	Sensor calibration adapter w/ tube and cup, 150 mL/min. regulator, 17L 2.5% methane, 17L 99.99% nitrogen, carrying case
<b>CALKIT-PG2-NO2</b>	Sensor calibration adapter w/ tube and cup, 500 mL/min. regulator (stainless steel), 70L 10 ppm nitrogen dioxide, 70L 99.99% nitrogen, carrying case
<b>CALKIT-PG2-CO-NO2</b>	Sensor calibration adapter w/ tube and cup, 500 mL/min. regulator (for CO), 500 mL/min. regulator (stainless steel, for NO2), 17L 200ppm carbon monoxide, 70L 99.99% nitrogen, 70L 10 ppm nitrogen dioxide, and (2) carrying cases

### Carrying Cases with Pre-Cut Foam

For (2) Gas Cylinders, Regulator and Connection Kit; Gas Cylinders Ordered Separately

<b>CC-STANDARD-17</b>	Briefcase style with foam inserts for 17L/34L/70L cylinders
<b>CC-STANDARD-58</b>	Briefcase style with foam inserts for 58L cylinders

### Gas Regulators

With Preset Flow Rate (mL/Min), On/Off Knob, Pressure Gage (Bar/Psi) & Hose Barb Outlet

<b>GR-17-150</b>	150 mL/min. flow rate with female threaded connection for gas cylinder
<b>GR-17-300</b>	300 mL/min. flow rate with female threaded connection for gas cylinder
<b>GR-17-500</b>	500 mL/min. flow rate with female threaded connection for gas cylinder
<b>GR-17-1500</b>	1500 mL/min. flow rate with female threaded connection for gas cylinder
<b>GR-58-400</b>	400 mL/min. flow rate with male threaded connection for gas cylinder
<b>GR-58-500</b>	500 mL/min. flow rate with male threaded connection for gas cylinder

### Tube/Cup Connector Kits for Gas Sensor Commissioning and Calibration

<b>CONKIT-AT6-CALCABLE</b>	AT6 calibration adapter cable
<b>CONKIT-COMB-AT</b>	For PolyGard®1 sensors combustible sensors including AT/DT5/SPC3-33xx
<b>CONKIT-E/CH-AT</b>	For PolyGard®1 sensors including AT/DT5/SPC3-1120/25-1129-1130
<b>CONKIT-E/CH-LC</b>	For PolyGard®1 CO and O2 sensors including LC/DT5/SPC3-1112 or AT/DT5/SPC3-1195
<b>CONKIT-IR-AT</b>	For PolyGard®1 AT-20XX series refrigerant sensors
<b>CONKIT-PG2</b>	For PolyGard®2 X-Change sensors (all gases)
<b>CONKIT-PX2</b>	For PolyXeta®2 X-Change sensors (all gases)
<b>CONKIT-TUB</b>	6-foot tubing only

**Warranty** Thirty days material and workmanship

## CC-, GR-, CONKIT AND CALKIT

CC-STANDARD-58



CC-STANDARD-17



GC...



CONKIT-PG2



GR...